


RI-02 Series Dry Reed Switch



RI-02 Series


Ultra-miniature dry-reed switch hermetically sealed in a gas-filled envelope. Single-pole, single-throw (SPST) type, having normally open contacts, and containing two magnetically actuated reeds.

The switch is of the double-ended type and may be actuated by an electromagnet, a permanent magnet or a combination of both.

The device is intended for use in relays, sensors, pulse counters or similar devices.

RI-02 Series Features

- ◆ Ideal for General Purpose reed relays and sensors
- ◆ Contact layers: ruthenium on gold
- ◆ Superior glass-to-metal seal and blade alignment



Dimensions in inches (mm)

General data for all models RI-02

AT-Customization / Preformed Leads

Besides the standard models, customized products can also be supplied offering the following options:

- Operate and release ranges to customer specification
- Cropped and/or preformed leads

Coils

All characteristics are measured using the Philips standard coil. For definitions of the Philips Standard Coil, refer to "Application Notes" in the *Reed Switch Technical & Application Information* Section of this catalog.

Life expectancy and reliability

The life expectancy data given below are valid for a coil energized at 1.25 times the published maximum operate value for each type in the RI-02 series.

No-load conditions (operating frequency: 100 Hz)

Life expectancy: min. 10^8 operations with a failure rate of less than 2×10^{-10} with a confidence level of 90%.

End of life criteria:

- Contact resistance $> 1\Omega$ after 2 ms
- Release time > 2 ms (latching or contact sticking).

Loaded conditions (resistive load: 5V; 100 mA; operating frequency: 125 Hz)

Life expectancy: min. 2×10^6 operations with a failure rate of less than 10^{-8} with a confidence level of 90%.

End of life criteria:

- Contact resistance $> 1\Omega$ after 2.5 ms
- Release time > 1 ms (latching or contact sticking).

Loaded conditions (resistive load: 20V; 500 mA; operating frequency: 125 Hz)

Life expectancy: min. 2×10^6 operations with a failure rate of $< 10^{-7}$ with a confidence level of 90%.

End of life criteria:

- Contact resistance $> 2\Omega$ after 2.5 ms
- Release time > 2.5 ms (latching or contact sticking).

Switching different loads involves different life expectancy and reliability data. Further information is available on request.

RI-02 Series Dry Reed Switch

| Model Number | | RI-02 | |
|--|-------------------|------------|-----------------|
| Parameters | Test Conditions | Units | |
| Operating Characteristics | | | |
| Operate Range | | AT | 7-21 |
| Release Range | | AT | 3-16 |
| Operate Time - including bounce (typ.) | (energization) | ms | 0.30 (25 AT) |
| Bounce Time (typ.) | (energization) | ms | 0.10 (25 AT) |
| Release Time (max) | (energization) | μ s | 70 (25 AT) |
| Resonant Frequency (typ.) | | Hz | 10800 |
| Electrical Characteristics | | | |
| Switched Power (max) | | W | 10 |
| Switched Voltage DC (max) | | V | 200 |
| Switched Voltage AC, RMS value (max) | | V | 140 |
| Switched Current DC (max) | | mA | 500 |
| Switched Current AC, RMS value (max) | | mA | 500 |
| Carry Current DC (max) | | A | 0.5 |
| Breakdown Voltage (min) | | V | 200-230 |
| Contact Resistance (initial max) | (energization) | m Ω | 150 (25 AT) |
| Contact Resistance (initial typ.) | (energization) | m Ω | 120 (25 AT) |
| Contact Capacitance (max) | without test coil | pF | 0.30 |
| Insulation Resistance (min) | RH \leq 45% | M Ω | 10 ⁶ |

Mechanical Data

Contact arrangement is normally open; lead finish is tinned; net mass is approximately 90mg; and can be mounted in any position.

Shock

The switches are tested in accordance with "IEC 68-2-27", test Ea (peak acceleration 150 G, half sinewave; duration 11 ms). Such a shock will not cause an open switch (no magnetic field present) to close nor a switch kept closed by an 80 AT coil to open.

Vibration

The switches are tested in accordance with "IEC 68-2-26", test Fc (acceleration 10G; below cross-over frequency 57 to 62 Hz; amplitude 0.75 mm; frequency range 10 to 2000 Hz; duration 90 minutes.) Such a vibration will not cause an open switch (no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

Mechanical Strength

The robustness of the terminations is tested in accordance with "IEC 68-2-21", test Ua₁ (load 10 N).

Operating and Storage Temperature

Operating ambient temperature; min: -55°C; max: +125°C. Storage temperature; min: -55°C; max: +125°C. **Note:** Temperature excursions up to 150°C may be permissible. For more information contact your nearest Coto Technology sales office.

Soldering

The switch can withstand soldering heat in accordance with "IEC 68-2-20", test Tb, method 1B: solder bath at 350 \pm 10° C for 3.5 \pm 0.5 s. Solderability is tested in accordance with "IEC 68-2-20" test Ta, method 3: solder globule temperature 235°C; ageing 1b: 4 hours steam.

Welding

The leads can be welded.

Mounting

The leads should not be bent closer than 1 mm to the glass-to-metal seals. Stress on the seals should be avoided. Care must be taken to prevent stray magnetic fields from influencing the operating and measuring conditions.