



RECOMMENDED PANEL MOUNTING



BOTTOM VIEW



CIRCUIT: DPDT

| SWITCH FUNCTION | | | |
|-----------------|--------|---------|--|
| POS. 1 | POS. 2 | POS. 3 | |
| (DN) | OFF | (DN) | |
| 2-3,5-6 | OPEN | 2-1,5-4 | |

NOTES:
 ()=Momentary

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.4VA @2D max. (AC or DC)
5. MATERIAL: FIXED TERMINAL & MOVING CONTACT
Copper Alloy w/Gold plate over Nickel plate.
6. CONTACT RESISTANCE: 10mILLI Ohms max initial @2-4VDC, 100mA for AG & AU
7. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
8. INSULATION RESISTANCE: 1,000M Ohm min.
9. DIELECTRIC STRENGTH: 1000V RMS @sea level
10. OPERATING TEMP.: -30°C to 85°C

E-SWITCH®

| | | | | |
|------|---------|---------------------------|---------|------|
| B | 12759 | DESCRIPTION WAS INCORRECT | 2/24/03 | CB |
| A | 12759 | RELEASED FOR PRODUCTION | 1/27/03 | CB |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |

| | | | | | | | | | | | | |
|-------|--|-----------------------------------|-------|-------|------|---------|----|----|-----|---------|-----|---|
| TITLE | | 300 DP-4 J3 M2 RE (GOLD CONTACTS) | SCALE | 1.5:1 | DATE | 1/27/03 | DR | CB | DWG | T324032 | REV | B |
|-------|--|-----------------------------------|-------|-------|------|---------|----|----|-----|---------|-----|---|

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED