



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
<DN>	OFF	<DN>
2-3	DPEN	2-1

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. CONTACT RATING: 5A, @120VAC or 28VDC; 2A, @250VAC.
  5. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
  6. INSULATION RESISTANCE: 1,000 M Ohms min.
  7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
  8. OPERATING TEMP.: -30°C to 85°C

# E-SWITCH®

300SP4U2BLKVS5QE

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	13013	RELEASED FOR PRODUCTION	4/9/03	AR

TITLE	SCALE	DATE	DR	DWG	REV
300SP4U2BLKVS5QE	2:1	4/9/03	AR	T314003	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED