


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
DN	OFF	(DN)
2-3	OPEN	2-1

()=Momentary

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING: 5A, @120VAC or 28VDC; 2A, @250VAC.
 5. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
 6. INSULATION RESISTANCE: 1,000 M Ohms min.
 7. DIELECTRIC STRENGTH: 1,000 V RMS @sed level.
 8. OPERATING TEMP.: -30°C to 85°C

C	15971	ADD *BLK* TO TITLE	5/1/06	BK
B	14309	CORRECT FRONT VIEW	9/10/04	AR
A	10123	RELEASED FOR PRODUCTION	2/15/99	MM
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE		DR		DWG		REV	
300SP5J3BLKV52QE		2:1		2/15/99		MM		T315003		C	



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED