


| PANEL THICKNESS | X |
|-----------------|------|
| 0.75-1.25 | 30.0 |
| 1.25-2.00 | 30.2 |
| 2.00-3.00 | 30.6 |

| SWITCH FUNCTION | |
|-----------------|--------|
| POS. 1 | POS. 2 |
| ON-ILLUMINATED | OFF |
| 1-1a | OPEN |

CIRCUIT: SPST
CONTACT CONFIGURATION



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 15A 250V, 20A 125V AC
5. MATERIAL: Body & Rocker: Nylon 6/6 UL94 V-2
6. LAMP VOLTAGE: 24VDC (Incandescent bulb)
7. MAJOR DIMENSION

| REV. | ECN NO. | DESCRIPTION | DATE | CHK'D | CJB |
|------|---------|--|---------|-------|-----|
| B | 12754 | REVISED RATINGS | 2/27/03 | CJB | |
| A | 12073 | RELEASED FOR PRODUCTION | 4/18/02 | CJB | |
| | | THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED | | | |

E-SWITCH®

TITLE: R4 B BLK BLK GRN E F 4

SCALE: 1:1 DATE: 3/21/01 DR: CJB DWG: M401126 REV: B