



SWITCH FUNCTION	
POS. 1	POS. 2
ON	OFF
2-1	OPEN

NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
- TERM. NOS. FOR REF. ONLY
- RATING: 16A, 125VAC, 10A, 250VAC UL&CUL APPROVED  
10A 125VAC, 6A 250V AC VDE APPROVED
- CONTACT RESISTANCE: 50m ohm max.
- INSULATION RESISTANCE: DC 500V 100M ohm min.
- DIELECTRIC STRENGTHS: AC 1500V 1 minute
- OPERATING TEMP.: 0°C to 85°C
- 3V RED LED
- ▲ DENOTES CRITICAL PARAMETER.

**E-SWITCH®**

B	13813	UPDATE PART AND NOTES	3/2/04	AR
A	13317	RELEASED FOR PRODUCTION	7/25/03	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE				
RR3112LBLKBLKREDEF3				
SCALE	DATE	DR	DWG	REV
2:1	7/25/03	AR	F130452	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED