


▲ HARDWARE SUPPLIED
DN SWITCH

NOTES:

1. ALL DIMENSION IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC
350mA, 110V AC/DC
5. CONTACT RATING (NON-SWITCHING) 5A
6. CONTACT MATERIAL: SILVER OVER COPPER ALLOY
7. OPERATING FORCE: 425±100 CM/STANDARD
8. OPERATING TEMP: -30° to +85°C
9. CIRCUIT SP: 2 POSITIONS, 30° INDEX
10. DIELECTRIC STRENGTH 1000V RMS min. @ SEA LEVEL
10. ▲ DENOTES CRITICAL PARAMETER.



E-SWITCH®

B	13132	6.35 WAS 6.00	5/13/03	AR
A	13080	RELEASED FOR PRODUCTION	4/24/03	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		DATE		DR		DWG		REV	
KC12A10.001NLS		4/24/03		AR		G527528		B	
SCALE		DATE		DR		DWG		REV	
1.5:1		4/24/03		AR		G527528		B	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED