


- NOTES:
1. ALL DIMENSION IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. CONTACT RATING SWITCHING: 150mA, 250V AC/DC
350mA, 110V AC/DC
 - ▲ 4. CONTACT RATING (NON-SWITCHING) 5A
 5. CONTACT: GOLD FLASH over Silver plated.
 6. OPERATING FORCE: 425±100 CM/STANDARD
 7. OPERATING TEMP: -30° to 85°C
 - ▲ 8. CIRCUIT SP: 3 POSITIONS, 90° INDEX.
 9. DIELECTRIC STRENGTH 1000V RMS min. @ SEA LEVEL
 10. ▲ DENOTES CRITICAL PARAMETER.
 - ▲ 11. HARDWARE SUPPLIED ON SWITCH- SEE BELOW
STOP RING, LOCKWASHER, & LOCKNUT



CONTACT CONFIGURATION
Timing: Non-Shorting

RECOMMENDED P.C.B. LAYOUT

E-SWITCH®

TITLE				
KC56A13.001NPF				
SCALE	DATE	DR	DWG	REV
1.5:1	10/1/03	AR	G511001	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED