


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPDT
CONTACT CONFIGURATION

SWITCH FUNCTION			
POS. 1	POS. 2	POS. 3	
DN	NONE	DN	
2-1	OPEN	2-3	

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 5A @120VAC or 28VDC; 2A @250VAC
 5. FIXED TERMINAL & MOVING CONTACT: Silver plated copper alloy.
 6. CONTACT RESISTANCE: 10m ohm typical.
 7. ELECTRICAL LIFE: 30,000 Actuations at full load.
 8. INSULATION RESISTANCE: 1,000 M ohm min.
 9. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
 10. OPERATING TEMP.: -30°C to 85°C.



REV. B		DIM 7.24 WAS 7.62		TITLE	
ECN No.		DESCRIPTION		500 SSP-1 S2 M2 Q E A	
11849		12/07/01		SCALE	
RSB		CHKD		2:1	
DATE		DATE		DATE	
2/16/00		MM		DWG	
DR		T511028		REV	
MM		B			

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED