


Ø1.85 HOLE
[.070] (3 PL)
RECOMMENDED P.C.B. LAYOUT



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 5A @120VAC or 28VDC;
2A @250VAC.
 5. FIXED TERM/MOVING CONTACT;
COPPER ALLOY W/ SILVER PLATE.
 6. ELECTRICAL LIFE: 30,000 make-and-break
cycles at full load.
 7. INSULATION RESISTANCE: 1,000M ohm min.
 8. DIELECTRIC STRENGTH: 1000V RMS @sea level
 9. OPERATING TEMP.: -30°C to +85°C

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
ON	NONE	ON
2-1	OPEN	2-3

D	14421	9.40 WAS 9.65	10/22/04	AR
C	13094	9.65 WAS 9.40	4/29/03	AR
B	11645	REVISED AND REDRAWN	3/6/02	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE: 500SSP1S3M2QEA

SCALE: 2:1	DATE: 3/6/02	DR: CJB	DWG: T511021	REV: D
------------	--------------	---------	--------------	--------