


NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
3. TERM NOS. FOR REF. ONLY
4. RATING: 0.4VA @20V max. (AC or DC)
5. CONTACT MATERIAL:
Copper Alloy w/Gold plate over
Nickel plate.
6. ELECTRICAL LIFE: 30,000 ACTUATIONS @Full Load
7. INSULATION RESISTANCE: 1000 Mega Ohms min.
8. DIELECTRIC STRENGTH: 1000V RMS @SEA LEVEL.
9. OPERATING TEMPERATURE: -30C TO 85C

CIRCUIT: SPDT



SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
DN	DN	DN
2-1	NONE	DN

RECOMMENDED P.C.B. LAYOUT

REV.	ECN No.	DESCRIPTION	DATE	CHKD	SCALE	DATE	DR	DWG	REV
B	11645	REVISED AND REDRAWN	9/6/01	CJB	2:1	9/6/01	CJB	TS14000	B
TITLE: 500 SSP-1 S4 M2 R E A (GOLD CONTACTS) THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED									

