


NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X-±0.4 X.XX-±0.25
3. TERM NOS. FDR REF. ONLY
4. RATING: 5A @120 (Resistive Load) 2A @250VAC
5. CONTACT MATERIAL: Copper Alloy w/Silver plate
6. ELECTRICAL LIFE: 30,000 ACTUATIONS @Full Load
7. INSULATION RESISTANCE: 1000 Mega Ohms min.
8. DIELECTRIC STRENGTH: 1000V RMS @SEA LEVEL.
9. OPERATING TEMPERATURE: -30°C TO 85°C

CIRCUIT, SPDT



SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
■	■	■	DN
□	□	□	OPEN

() =Momentary

E-SWITCH®

B	12697	REV. MDM FUNC WAS PDS 1	1/7/03	CJB
A	11606	RELEASED FOR PRODUCTION	8/9/01	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

SCALE	2:1	DATE	8/9/01	DR	CJB	DWG	T522006	REV	B
TITLE	500 SSP-2 S4 M7 Q E A								

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED