



CIRCUIT: SPDT
CONTACT CONFIGURATION

| SWITCH FUNCTION | | | |
|-----------------|--------|--------|--|
| POS. 1 | POS. 2 | POS. 3 | |
| DN | OFF | DN | |
| 2-1 | OPEN | 2-3 | |

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 0.4(VA) max. @20V max. (AC or DC)
5. TRAVEL TO MAKE: 2.16 [.085]

| | | | | |
|------|---------|-------------------------|------|------|
| REV. | ECN NO. | DESCRIPTION | DATE | CHKD |
| A | 10454 | RELEASED FOR PRODUCTION | | |

| | | | | | |
|-----------------------|-------|---------|----|----------|-----|
| TITLE | SCALE | DATE | DR | DWG | REV |
| 500 SSP-3 S1 M6 R E A | 2:1 | 12/7/99 | MM | T5222004 | A |

E-SWITCH®

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED