


RECOMMENDED P.C.B. LAYOUT



CIRCUIT: DPDT

CONTACT CONFIGURATION

SWITCH FUNCTION	
PDS. 1	PDS. 2
DN	DN
2-1,5-4	2-3,5-6

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. CONTACT RATING: 0.4 VOLT-AMPS(VA) MAX@20V MAX (AC OR DC)
  5. FIXED TERM & MOVING CONTACT:  
COPPER ALLOY W/GOLD PLATE OVER NICKEL PLATE
  6. CONTACT RESISTANCE: 50MΩ MAX
  7. MECHANICAL LIFE: 20,000 OPERATIONS
  8. INSULATION RESISTANCE: 1000 MΩ UNDER 500V
  9. OPERATING TEMP: -40°C TO 85°C
  10. BREAKING CAPACITY: 400 MA 20V

D	15163	CHANGED DIMENSION	8/9/05	PV
C	11718	REVISED, AND REDRAWN	10/09/01	CJC
REV.	ECN NO.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE		DR		DWG		REV	
600 DP1 S1 M2 R E		2:1		10/09/01		CJC		T620001		D	
<b>E-SWITCH®</b>											
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED											