



CONTACT CONFIGURATION

SWITCH FUNCTION	PDS: 1	PDS: 2
DN	DN	DN
2-1,5-4	2-3,5-6	

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. CONTACT RATING: 5A@ 120VAC OR 28VDC
1A@ 250 VAC
 5. FIXED TERM & MOVING CONTACT:
COPPER ALLOY W/SILVER PLATE
 6. CONTACT RESISTANCE: 10MΩ MAX
 7. MECHANICAL LIFE: 20,000 OPERATIONS
 8. INSULATION RESISTANCE: 1000 MΩ UNDER 500V
 9. OPERATING TEMP: -40°C TO 85°C
 10. BREAKING CAPACITY: 1A 30VDC

E-SWITCH®

TITLE: 600 DP1 S1 M4 Q E

REV.	ECN No.	DESCRIPTION	DATE	CHKD
B	11718	REVISED, AND REDRAWN	10/09/01	CJC

SCALE	DATE	DR	DWG	REV
2:1	10/09/01	CJC	T620003	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED