


RECOMMENDED P.C.B. LAYOUT



CIRCUIT: DPDT

CONTACT CONFIGURATION

SWITCH FUNCTION	
PDS. 1	PDS. 2
DN	DN
2-1,5-4	2-3,5-6

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.XX=±0.4 X.XX=±0.25
3. TERM. NDS. FOR REFERENCE ONLY.
4. CONTACT RATING: 0.4 VOLT-AMPS(VA) MAX@20V MAX (AC OR DC)
5. FIXED TERM & MOVING CONTACT: COPPER ALLOY W/GOLD PLATE OVER NICKEL PLATE
CONTACT RESISTANCE: 50MΩ MAX
MECHANICAL LIFE: 20,000 OPERATIONS
INSULATION RESISTANCE: 1000 MΩ UNDER 500V
OPERATING TEMP: -40°C TO 85°C
BREAKING CAPACITY: 400 MA 20V

REV.	ECN No.	DESCRIPTION	DATE	CHKD
B	11718	REVISED, AND REDRAWN	10/09/01	CJC

TITLE	SCALE	DATE	DR	DWG	REV
600 DP1 S3 M4 R E	2:1	10/09/01	CJC	T622003	B



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED