


RECOMMENDED P.C.B. LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION	POS. 1	POS. 2
DN	2-1	2-3

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. CONTACT RATING: 5A@ 120VAC OR 28 VDC
1A@ 250 VAC
 5. FIXED TERM & MOVING CONTACT:
COPPER ALLOY W/SILVER PLATE
 6. CONTACT RESISTANCE: 10MΩ MAX
 7. MECHANICAL LIFE: 20,000 OPERATIONS
 8. INSULATION RESISTANCE: 1000 MΩ UNDER 500V
 9. OPERATING TEMP: -40°C TO 85°C
 10. BREAKING CAPACITY: 1A 30 VDC

E-SWITCH®

REV.	ECN NO.	DESCRIPTION	DATE	CHKD
C	16058	EDIT DIMENSIONS	5/30/06	CT
B	11718	REVISED, AND REDRAWN	10/08/01	CJC

TITLE	SCALE	DATE	DR	DWG	REV
600 SP1 S3 M1 Q E	2:1	10/08/01	CJC	T613000	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED