



SPECIFICATIONS AND OPTIONAL FEATURES

TYPE	CIRCUIT	ELECTRICAL RATING	UL & CSA
G-107-SI-0511	SPDT	.5A AC DC 125V	APPROVED

BUTTON OPTIONS

LENGTH	PART NUMBER	COLOR
.140 (3.56mm)	G-02-240-1 is Standard	BLACK
.200 (5.08mm)	G-02-240-2	BLACK
.250 (6.35mm)	G-02-240-3	BLACK
.250 (6.35mm)	G-02-240-4	BLue
.250 (6.35mm)	G-02-240-5	Red

TERMINALS

Standard solder terminal also mates with AMP connector 62343-1.

MOUNTING

Snaps directly into panel having hole piercing as shown.  
Designed for panel thickness of .047, .062, .078 and .093.

FORM-B

REVISIONS
0
1

RELEASED 1-8-85 GZ

.360±.010 WAS .400±.010 AND 9.14±.25 WAS 10.16±.25. NM 7-24-85 JUL. 28.1986

PDF File Made	<b>ew INDUSTRIES</b> Southampton, Pa. 18966		Title: <b>SNAP-IN SLIDE SWIDGET JR. ASSEMBLY S.P. - D.T.</b>
	TOLERANCES UNLESS OTHERWISE SPECIFIED		
	2 Place decimal ±.010	METRIC	Division: <b>SWITCH</b>
	3 Place decimal ±.005	1 Place dec. ±.25mm	
	Angles ..... ± 1°	2 Place dec. ±.13mm	
Made for: CW	Drawn by: B.DeRosier 1-4-85	Dwg. No. <b>G-107-SI-0511</b>	
Checked by: CH 1-7-85	Approval: GZ 1-8-85		