



8LS1
 PAGE 1 OF 1
 M
 DRAWING NUMBER
 ISSUE 17
 REVISIONS
 A CO 15200
 O M W
 18 JUN 65
 B CO 23403
 G F S
 26 SEPT 68
 C CO 24612
 R E R
 15 OCT 68
 D CO 25152
 W A W
 19 APR 69
 E CO
 50952-F
 T S K
 9 JUNE 83
 F CO
 53005-D
 C J H
 AUG 84
 G CO
 65814-E
 G R T
 26 NOV 90
 H CO
 77031
 J D B
 22 DEC 93
 J CO 94494
 J A F
 19 MAR 99
 O M W 18 JUN 65
 DRAWN
 FORMTEK
 FO-80378-003

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE 1/2 TO 1
OPERATING FORCE ----- 5 OZ MAX	CONTACT ARRANGEMENT (SEE CIRCUIT DIAGRAM)	DO NOT SCALE PRINT
FORCE AT 2.0 ----- 10 OZ MAX	10A-120, 240, OR 480 VAC; 1/4 HP - 120 VAC 1/2 HP - 240 VAC; 0.8A - 115 VDC; 0.4A - 230 VDC .1A - 550 VDC PILOT DUTY: 600 VAC MAX	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ± .030 TWO PLACE (.00) ± .015 THREE PLACE (.000) ± .005 ANGLES ±
SWITCH - BASIC REPLACEMENT ----- 2MN11		WEIGHT

NOTE -
 SEAL TO BE FURNISHED BY USER