



**NOTE**  
△ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON  $1.000 \pm .002$  CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL
OPERATING FORCE ----- 9-13 OZ	CONTACT ARRANGEMENT S P D T	DO NOT SCALE PRINT
RELEASE FORCE ----- 4 OZ MIN	15A - 125, 250 OR 480 VAC, 2A - 600 VAC 1/8HP - 125 VAC; 1/4HP - 250 VAC CODE L74 1/2A - 125 VDC; 1/4A - 250 VDC	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES <b>TOLERANCES ARE:</b>
DIFFERENTIAL TRAVEL -- .0004 - .0020	-L288-     EN05 -L306-    16A 250V ~ T85 5E4 -L315-	ONE PLACE (.0)    ±.030 TWO PLACE (.00)    ±.015 THREE PLACE (.000)    ±.005 ANGLES    ±
OVERTRAVEL ----- .219 MIN		WEIGHT .120 LB

**FORMTEK**  
FO-80376

**BZ-2RQ66**  
PAGE 1 OF 1

**M**  
DRAWING NUMBER

8  
ISSUE

REPLACES

RELEASE NO.

CHECK

29 AUG 05

REVISIONS

A	C017410	LLD	27 MAR 64
B	C034353	BEN	1 NOV 74
C	C036099	P	6 JUN 77
D	CO-73287-8	DHD	17 MAY 93
E	CO-77592	DAW	15 AUG 94
F	C093346	DLT	1 SEP 98
G	0015138	SPK	29 AUG 05

CHECK

RJ

2, APR 64

DRAWN

27 MAR 64

CHECK

LLD