



CIRCUIT: SPDT  
CONTACT CONFIGURATION

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 1A @125/250V AC
5. CONTACT MATERIAL: SILVER
6. OPERATING FORCE: 60gf Typical.
7. ELECTRICAL LIFE: 300,000 Cycles min.
8. INSULATION RESISTANCE: 100 Mega-ohms min.
9. DIELECTRIC STRENGTH: >1000 V RMS @ SEA LEVEL
10. OPERATING TEMP.: -25°C to 85°C

*O.P. (mm)	*P.T. (mm)
5.5 +/-0.5	0.5 Max.

\*O.P. = Operating Point  
\*P.T. = Pre-Travel

RECOMMEND P.C.B. LAYOUT

REV.	ECN No.	DESCRIPTION	DATE	CHK'D
B	12050	REVISED AND REDRAWN	4/10/02	CB

TITLE	SCALE	DATE	DR	DWG	REV
DM085 01 00 F060 P1A-YEL	4:1	4/10/02	CB	P030005	B



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED