


RECOMMENDED P.C.B. LAYOUT



CIRCUIT: SPST  
CONTACT CONFIGURATION

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATINGS: 50mA @12VDC
5. CONTACT/TERMINATION MATERIAL: Silver
6. CONTACT RESISTANCE: 100 Ohms max.
7. OPERATING FORCE: 160±50gf.
8. TRAVEL: 0.25±0.1mm
9. DESIGNATE MAJOR: ▲

**E-SWITCH®**

| REV. | ECN NO. | DESCRIPTION              | DATE     | CHKD |
|------|---------|--------------------------|----------|------|
| C    | 12542   | REVISED PER CATALOG DESC | 11/6/02  | CJB  |
| B    | 12510   | REVISED MATERIAL SPEC    | 10/25/02 | CJB  |
| A    | 11568   | RELEASED FOR PRODUCTION  | 7/13/01  | CJB  |

| TITLE                            | SCALE | DATE    | DR | DWG     | REV |
|----------------------------------|-------|---------|----|---------|-----|
| TLE1105 F160 Q (ACTUATOR =4.3mm) | 4:1   | 7/13/01 | CB | D310100 | C   |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED