


RECOMMENDED MOUNTING PAD

SCALE: 4:1



CIRCUIT: SPST

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 50mA, @12V DC
5. MATERIAL: PPS RYTON R-4
6. OPERATING FORCE: 160gf +50/-30grams
7. TRAVEL: 0.25 +0.2/-0.1mm
8. CONTACT RESISTANCE: 100 ohms max.
9. PACKAGED: TAPE & REEL QTY 1100



REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	11570	RELEASED FOR PRODUCTION	7/17/01	CB

TITLE	SCALE	DATE	DR	DWG	REV
TL 3301 A F160 Q J (TAPE & REEL)	3:1	7/17/01	CB	P010508	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

DETAIL A
SCALE 6:1

FLUSH WITH SURFACE -A- TO BELOW.

0.43 Max. (.017)