



CIRCUIT: SPDT CONTACT CONFIGURATION

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
<ON>	OFF	<ON>
2-3	OPEN	2-1

NOTES:

1. ALL DIMENSIONS IN INCH (MM)
2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
4. TERM. NOS. FOR REF. ONLY
5. RATING: 0.4(VA) max. @20V max. (AC or DC)
6. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
7. INSULATION RESISTANCE: 100M Ohm min.
8. DIELECTRIC STRENGTH: 1000V RMS min. @sea level
9. OPERATING TEMP.: -30°C to 85°C
10. ▲ DESIGNATE MAJOR FEATURE

< >=MOMENTARY

**E-SWITCH®**

D	10864	ADD NOTE	8/17/00	MM
C	10711	EPOXY LOCATION DEFINE	6/27/00	MM
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE				
200A WMSP-4 T2 A1 M61 R E				
SCALE	DATE	DR	DWG	REV.
2:1	8/17/99	MM	T201406	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED