

Scotch® High Performance Printed Box Sealing Tape



3732 • 3734

Technical Data

April, 2003

Product Description

Scotch® Box Sealing Tape 3732 and 3734 is a high performance packaging tape used for box sealing, splicing, recoupage, and other demanding packaging applications. This product has a heavy-duty, conformable backing and the most consistent pressure sensitive hot melt adhesive system available. Scotch® Tape 3732 prominently exhibits a random printed message: IF SEAL IS BROKEN CHECK CONTENTS BEFORE ACCEPTING. Scotch® Tape 3734 prominently exhibits a random printed message: FRAGILE HANDLE WITH CARE.

Construction

Backing	Adhesive	Colors
Biaxially oriented 3M™ Scotchpro™ polypropylene film	Pressure sensitive hot melt rubber-resin	Tan with red printed message

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	50 oz./in. width (55 N/100 mm width)	D-3330
Tensile Strength:		
Machine Direction:	30 lbs./in. width (525 N/100 mm width)	D-3759
Cross Direction:	60 lbs./in. width (1050 N/100 mm width)	D-3759
Elongation at Break:	160%	D-3759
Thickness - Backing:	1.6 mil (0.041 mm)	D-3652
Total:	2.5 mil (0.064 mm)	D-3652
Holding Power to Fiberboard:	8,000 + minutes	D-3654

Features

- Adheres instantly to a wide variety of surfaces.
- High edge tear and split resistance.
- Communicates the need for careful package inspection prior to acceptance.
- Complies with the environmental considerations of ASTM D 1974-92.
- High performance ensures reliable closures.
- Reduction to merchandise lost through pilferage.
- Reliable closures reduce damaged goods during shipment.

Scotch® High Performance Printed Box Sealing Tape

3732 • 3734

Available Sizes	Standard Widths:	48 mm Custom widths available upon request.
	Core Size (ID):	3 in.
	Lengths:	50 m, 914 m

Application Techniques An extensive line of application equipment including hand held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® Box Sealing Tape 3732 and 3734 is most easily accomplished at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, these tapes perform well throughout the normal temperature range encountered by packaged products in shipping and storage environments.

Storage Conditions Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business
Industrial Adhesives and Tapes Division**
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2003 70-0710-0207-8 (4/03)