

# Tartan<sup>TM</sup> Label Protection Tape 3765

Technical Data

June, 2003

**Product Description** Tartan<sup>TM</sup> Label Protection Tape 3765 is a utility-grade label protection tape with a clear, strong, moisture-resistant film backing and a clear adhesive that holds well to many treated and finished surfaces. This tape may be used for attachment and preservation of identifying labels in shipping, storage, and manufacturing applications.

Construction	Backing	Adhesive	Colors
	Biaxially oriented polypropylene film	Pressure sensitive acrylic	Clear

## Typical Physical Properties

**Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	22 oz./in. width (24 N/100 mm width)	D-3330
Tensile Strength:		
Longitudinal:	20 lbs./in. width (350 N/100 mm width)	D-3759
Transverse:	30 lbs./in. width (525 N/100 mm width)	D-3759
Elongation at Break:	119%	D-3759
Total Thickness:	1.5 mil (0.038 mm)	D-3652

**Note:** Utility-grade Tartan<sup>TM</sup> Tapes have physical properties that may vary over a broad range.

## Features

- Adheres instantly to a variety of surfaces.
- Edge tear and split resistance.
- Conformable backing.
- Good adhesion at 40°F (4°C).
- Complies with environmental consideration of ASTM D1974-92.
- Acrylic adhesive stays clear and is UV-resistant.
- Clear protection of labels from smudging, splashing, and tearing.
- This tape holds well up to 220°F (104°C) and in cold temperatures.
- Clear surface allows sharp bar code read.
- A great choice for outdoor protection applications.

# Tartan™ Box Sealing Tape

3765

---

<b>Available Sizes</b>	Standard Widths:	72 mm, 96 mm, 120 mm, 144 mm
	Core Size (ID):	3 in.
	Lengths:	132 m

---

**Storage Conditions** Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended.

---

**For Additional Information** To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit [www.3M.com/packaging](http://www.3M.com/packaging). Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

---

**Important Notice** 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

---

**Limitation of Remedies and Liability** If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.

ISO 9002

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business**  
**Industrial Adhesives and Tapes Division**  
3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000



*Recycled Paper*  
40% pre-consumer  
10% post-consumer

Printed in U.S.A.  
©3M 2003 70-0710-0232-6 (6/03)