



1205 Tape

Polyimide Film With Acrylic Adhesive

Data Sheet

Product Description

3M™ 1205 Tape is a 1-mil polyimide backing with acrylic adhesive. It is designed for high-temperature applications, in which a solvent-resistant backing is required, used on coils, capacitors and wire harnesses.

- 1-mil polyimide Kapton™ backing
- Acrylic adhesive
- Supplied on 3 inch cores

3M 1205 Tape is available in standard and custom widths and lengths. Standard length is 36 yards.

- Widths from 1/4" to 23"
- Longer lengths up to several times normal length, dependent upon width. Check with Customer Service.

Applications

3M 1205 Tape is used for high-temperature electrical applications in which a tough, thin insulating material that is solvent resistant is required for wrapping coils, transformers, capacitors and wire harnesses. It is also used as a cover layer material for many types of flexible printed circuits.

Properties

Typical Values

Adhesive	Acrylic
Backing	Polyimide
Backing Thickness ¹	One Mil
Total Thickness	3.0 mils/.076mm
Operating Temperature (continuous)	155°C/311°F
Dielectric Breakdown ¹	7,500 Volts
Insulation Resistance ¹ (megohms)	>1 x 10 ⁶
Breaking Strength ¹	30 lbs./in. (53 n/10mm)
Elongation ¹ (% at break)	55
Electrolytic Corrosion Factor ³	1.0
Adhesion to Steel ¹	35 oz./in. (3,8 n/10mm)
UL 510 Flame Retardant ²	Yes

* Footnote: 1. Test method ASTM D 1000
2. UL-recognized for flame retardancy per UL 510, Product Category 0ANZ2, File E17385.
3. 3M Test Method-Available on request

3M is a trademark of 3M.

Important Notice

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller.

The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.



Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
800 676 8381
<http://www.3m.com/elpd>

© 3M 1998
78-8124-4706-4