



High Temperature Aluminum Foil/Glass Cloth Tape

363 • 363L (Linered)

Technical Data

July, 2008

Product Description 3M™ High Temperature Aluminum Foil/Glass Cloth Tape 363 can be used as a high temperature, heat reflective, protective wrap for certain cables and other components in aerospace and industrial applications.

Product Construction	Backing	Adhesive	Color	Liner (3M tape 363L)	Standard Roll Length
	Aluminum foil laminated to glass cloth	Silicone (transparent)	Shiny silver	Transparent, easy-release film	36 yds. (33 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	52 oz./in. width (57 N/100 mm)	D-3330
Tensile Strength:	135 lbs./in. width (2364 N/100 mm)	D-3759
Elongation at Break:	7%	D-3759
Backing Thickness:	Foil: 1.0 mil (0.025 mm) Glass Cloth: 2.4 mils (0.06 mm)	D-3652
Total Tape Thickness:	7.3 mils (0.19 mm)	D-3652
Liner Thickness: (3M tape 363L)	2.0 mils (0.05 mm)	D-3652
Temperature Use Range:	-65° to 600°F (-54 to 316°C)	
Weight:	0.0114 lbs./yd./in. width (0.0057 kg/m/24mm)	

Features

- Can easily be die-cut into special sizes or shapes.
- Light, flexible construction – easily applied to a variety of irregular shapes.
- Performs continuously from -65°F (-54°C) to over 600°F (316°C).
- Meets the requirements of F.A.R. 25.853(a).
- Best results obtained when applied to a clean dry surface above 32°F (0°C), but can be applied at lower temperatures.

Application Ideas

- A heat reflective wrap, over insulation cables, instruments, or other high temperature sensitive materials.

3M™ High Temperature Aluminum Foil/Glass Cloth Tape

363 • 363L (Linered)

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 36 months from date of manufacture.

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Warranty, Limited Remedy, and Disclaimer Many factors beyond 3M's control and uniquely with user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M company.
Printed in U.S.A.
©3M 2008 70-0709-4996-4 (7/08)