

Scotch[®] Solvent Resistant Masking Tape Black 226



Technical Data

May, 2003

Product Description

Scotch[®] Solvent Resistant Masking Tape 226 is a black polyethylene film reinforced with a saturated crepe paper for outdoor masking and hot air leveling of printed circuit boards. The polyethylene backing is resistant to many solvents, water solutions and emulsions, and paint strippers of the wax-base type and the mild caustic solution solvent-emulsion type.

Construction

Backing	Adhesive	Color	Standard Roll Length
Black polyethylene/ saturated crepe paper	Rubber	Black	60 yds. (55 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	40 oz./in. width (43 N/100 mm width)	D-3330
Tensile Strength:	33 lbs./in. width (578 N/100 mm width)	D-3759
Elongation at Break:	8%	D-3759
Tape Thickness:	.010 in. (0.25 mm)	D-3652
Temperature Use Range:	Up to 250°F (121°C) for 30 minutes	

Features

- Excellent weathering properties up to three months on all surfaces except Plexiglas or other surfaces which transmit sunlight.
- Bakelized synthetic adhesive with instant adhesion/good holding power and stain resistant to help minimize labor and reduce rework.
- Weather, sunlight and UV resistant for clean removal after outdoor exposure.
- Saturated crepe paper that reinforces, controls stretch and tear to help save time and money/excellent handling and performance.

Application Ideas

- Outdoor protection of metal and painted surfaces up to a period of three months.
- Sealing operations of plastic tarps, access holes in appliances, concrete encased duct work, etc.
- Masking operations involving solvents, water solutions, and emulsions in the aircraft industry.

Scotch® Solvent Resistant Masking Tape Black

226

Storage Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Shelf Life To obtain best performance, use Scotch® Solvent Resistant Masking Tape 226 within one year from date of manufacture.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/industrialtape. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9002

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.

3M

**Industrial Business
Industrial Adhesives and Tapes Division**
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2003 70-0709-5156-4 (5/03)