

Temperature Accessories

Contact Probes

80PK-1 and 80PJ-1 Bead Probe

- 80PK-1: Type-K thermocouple for general purpose applications
- 80PJ-1 operates with J-type thermometers
- Measurement range: -40 to 260°C



80PK-5A and 80PT-5A Piercing **Probe**

- 80PK-5A: Type-K thermocouple suitable for food industry, liquids and gels except halides
- 80PT-5A operates with T-type thermometers
- Measurement range: -40 to 260°C



80PK-8 Pipe Clamp Temperature Probe

- Type-K thermocouple for fast temperature and superheat measurements of pipe surfaces
- Durable ribbon sensor
- Measurement range: -29 to 149°C for pipe diameters from 6.4 to 34.9mm



80BK Low-cost Integrated DMM Probe

- Type-K thermocouple with standard banana iack
- Convenient one piece construction
- Compatible with DMMs with temperature measurement functions
- Measurement range : -40 to 260°C



80PK-6A Exposed Probe

- Type-K thermocouple provides fast response for non-reducing air and gases, except halides, sulfides, and vacuums
- Measurement range: -40 to 816°C



80PK-9 and 80PJ-9 General **Purpose Probe**

- 80PK-9: Type-K thermocouple surface, air and non-caustic gases
- 80PJ-9 operates with J-type thermometers
- Measurement range : -40°C to 260°C

80PK-2A Immersion Probe

80PK-3A Surface Probe

• Type-K thermocouple for

flat or curved surfaces such as

 Measurement range: 0 to 260°C

plates and rollers

- Type-K thermocouple for use in liquids and gels
- Measurement range: -40 to 982°C



80PK-7 Industrial Surface Probe

- Type-K thermocouple for surfaces in rugged environment
- Durable ribbon sensor
- Measurement range: -127 to 600°C



80T-150U Universal Temperature Probe

- Compatible with Fluke DMM
- · High accuracy, fast reading for low voltage (below 24Vac, 60V dc) applications
- Measurement range: -50 to 150°C
- ◆ Output: 1mV/°C or 1mV/°F (switchable)



80PK-4A Air Probe

- Type-K thermocouple for use in air or gases, except halides and sulfides
- Bead protected by perforated baffle
- Measurement range: -40 to 816°C



80TK Thermocouple Module

- Converts a DMM to a thermometer
- For use with type-K thermocouples in low voltage applications (below 24Vac, 60V dc)
- Measurement range: -50 to 1000°C (probe dependent)



Temperature Accessories

Non-Contact Probes

80T-IR & 80PK-IR Infrared Temperature Probes

- Ideal for applications where object being measured cannot be touched
- Provides instant and highly repeatable readings
- 80T-IR (for DMMs) and 80PK-IR (for digital thermometers) have automatic shut-off after 10 minutes
- Senses infrared energy emitted by an object
- Measurement range: -18 to 260°C





Other Temperature Accessories

80CK-M & 80CJ-M type K & J Male Mini-Connectors

- Isothermal screw terminal for K or J wire
- Suitable for up to 20 guage thermocouple wire
- Color coded to industry standards (K-yellow, J-black)
- Two per package



80AK

- Adapts Type-K thermocouple mini-connector to dual banana plug inputs
- Measurement range and accuracy: probe dependent
- Suitable for low voltage applications (below 30V AC, 60V DC)



80PK-EXT, 80PJ-EXT and 80PT-EXT Extension Wire Kits

- Extending and repairing J, K ot T-type thermocouple wires
- Kit includes 3 meters of thermocouple wire and 1 pair of male/female mini-connectors
- Maximum continuous exposure temperature : 260°C
- 80PK-EXT is compatible with K-type thermometers, 80PJ-EXT is designed for Jtype thermometers and PT-EXT for T-type thermometers



Thermocouple Plug Kits 700TC1

A kit of 10 mini-plug connectors
Type J (black), one
Type K (yellow), one
Type T (blue), one
Type E (purple), one
Type R/S (green), one
Type B or CU (white), one
Type L (J-DIN) (blue), one
Type U (T-DIN) (brown), one
Type C (red), one
Type N (orange), one

700TC2

A kit of 7 mini-plug connectors Type J (black), two Type K (yellow), two Type T (blue), one Type R/S (green), one



Temperature Probe Compatibility Chart																																		۱S	
Contact Probes	7-300 / 7-600	10 / 11 / 12 / 12B	16	27	70 Series III	ies III	21/75 Series III	23/77 Series III		83 Series III	85 Series III		187 Series	189 Series	867B	39 / 41B	123	190 Series	45	45 50¢/50D	51/52/53/54 series II	33/3	705	712	713	714	715	716	717	718	725	741B	743B	744	787
80PK-1 through 80PK-9		\vdash	2	+	1	+	1	1 -	+	+	+	+	2	2	1	\rightarrow	1	,	, ,		•	+	+-	-		•		+	+	-		•	•	•	+
80T-150U	\vdash			<u></u>	<u>+</u>	-	<u> </u>	<u> </u>			+	÷		4	1	\rightarrow	1	•		-	4	+	+	-		•	•	+	+	-		. + =	. + =		
80PJ-1, 80PJ-9		_	-+	"	•	┵'	•	•	4	, •	╨	-	•	•	•	\rightarrow	•	<u> </u>	•	-	•	+	+			•	•	+	+			.#			+-
80PJ-5A		\rightarrow	\rightarrow	+	\rightarrow	+	+	+	+	+	+	+		\rightarrow		\rightarrow	-+	-	+	ս-Ի	4	-	+-	-		÷		+	+						
80BK	\vdash	\vdash	•	+	\rightarrow	+	+	+	+	+	+	+	•		-	\rightarrow	\rightarrow	\rightarrow	+	+	┵	+	+	-		•	-	+	+	+	′+•	+-	+-	_	+
Non-Contact Probes		\vdash	•	+	\dashv	+	+	+	+	+	+	\vdash	•	•	-	\rightarrow	-	+	+	+	+	+	+					+	+	+	+	+	+	+	+
80T-IR			•						-	•	-		•	•		\rightarrow	•	•		+	+	+	•				•	+	+	-		•			•
80PK-IR	\vdash	_	2	-	-	₹,	₹		+	_	+	۳	2	2	_	\rightarrow	-	<u> </u>	-	1	•		+	 		•	-	+	+						•
Miscellaneous		-		+	-+	+	+	+	+	+	+	+				\rightarrow		-	+	+	_	+	+	1	H	•		+	+	+	_	+	+	+	+•
80AK		\vdash	•	+	+	+	+	+	+	+	+	+	•	•	-	\dashv	-	+	+	+	+	+	+	 				+	+	+	+	+	+	+	+
80TK	\vdash					-	•		-	•	1				•	\rightarrow	•	•		+	+	+	•		\vdash		•	+	+	1					•
80CK-M			-	- 	-	₹,	₹,	-	₩	+▼	+	۳		-	_	\dashv	_	- `	-	1	•		+	<u> </u>		•	-	+	+	+	. i	. -			
80CJ-M		\vdash	+	+	+	+	+	+	+	+	+	+		\rightarrow	-	\dashv	\rightarrow	+	+		•		+	 		÷		+	+	+	Hě	.+*	_	•	-
80PK-EXT, 80PJ-EXT		-	-	+	\pm	+	+	+	+	+	+	\vdash				\rightarrow		+	_				+			÷		\pm	+	+	•	•		•	
80PT-EXT		-	-+	\rightarrow	-+	-	-	-	+	-	+-	+		-	_	-	_	_	-			+	+	+	\vdash	÷	-	-	+		•			•	

Pub_ID: 10015-eng

Rev. 02

1: Requires 80TK 2: Requires 80AK





this product is available from:



Thurlby Thandar Instruments Ltd.

Glebe Road, Huntingdon Cambs. PE29 7DR England

Tel: 01480 412451 Fax: 01480 450409

email: sales@tti-test.com web: www.tti-test.com

TTi is an official technical distributor for the Fluke Test Tools and Bench Instruments range in the UK.

We aim to keep many of the most popular products in stock for immediate delivery.

We can provide technically based advice on the use of these products and our sales engineers will be pleased to arrange a demonstration.



Measurably Better Value