

50,000 Count Premium DMM



The 5300 Series handheld DMM is the most advanced digital multimeter available in this price range. These meters incorporate a special 50,000 count integrated circuit for high-accuracy (0.025%) basic accuracy, high-reliability design. Measure AC Volts (True RMS AC, AC + DC), Resistance, Capacitance and Frequency, in addition to dB, Duty Cycle, Pulse Width, Power Line Disturbances and Temperature. These meters also feature fuse and battery access without breaking a calibration seal, great for ISO facilities. All models offer Peak Hold, Hold, Relative Mode and Backlight.

- Precision 50,000 count instruments
- 0.025% Basic DCV accuracy (Models 5380 and 5390)
- True RMS reading
- Large LCD display provides easy readability, all test parameters in clear view.
- Best value of any DMM
- CE safety approved

Features		models			
	5390	5380	5370	5360	
Basic Functions					
Basic Accuracy		0.025%	0.05%	0.1%	
Voltage (Best Resolution)		750VAC/1000VDC (10µV)		750VAC/1000VDC (100µV)	
Current (Best Resolution)		10AAC/DC (10nA)		10AAC/DC (1µA)	
Frequency	√		√		
Temperature Probe			√		
Duty Cycle	√		√	√	
Event Counter	√				
Backlight	√	√	√		

Specifications		models					
	5390	5380	5370				
AC VOLTAGE (Auto/Manual Ranging, True RMS) Modes: AC or AC+DC, selectable							
Accuracy at greater than 10% of range, 50,000 counts at Full Scale:							
Ranges	DC to 1kHz	1 kHz to 4 kHz	4 kHz to 10 kHz	10 kHz to 30 kHz	30 kHz to 50 kHz	Resolution	Input Impedance
500 mV	0.3%R+30D	1%R+3D	5%R+30D	Not specified		10µV	10 MΩ/100 pF or 1 GΩ
5V	0.3%R+30D	1%R+3D	2%R+30D	2%R+30D	3%R+30D	100 µV	11 MΩ/100 pF
50V	0.3%R+30D	1%R+30D	2%R+30D	2%R+30D	3%R+30D	10 MΩ/100 pF	
500V	0.3%R+30D	1%R+30D	2%R+30D	2%R+30D	3%R+30D	10 MΩ/100 pF	
750V	0.3%R+30D		Not specified			100 mV	10 MΩ/100pF
50 kHz to 100 kHz (5V, 50 V, 500 V ranges): ±6% FS typical Crest Factor: 6							

		model					
	5360						
Accuracy at greater than 10% of range, 5,000 counts at Full Scale:							
Ranges	DC to 1kHz	1 kHz to 5 kHz	5 kHz to 10 kHz	10kHz to 20 kHz	20 kHz to 30 kHz	Resolution	Input Impedance
500 mV	1%R+3D	4%R+3D		Not specified		100µV	10 MΩ/100 pF
5V	1%R+3D	1%R+3D	2%R+30D	2%R+3D	3%R+3D	1 mV	11 MΩ/100 pF
50V	1%R+3D	1%R+3D	2%R+30D	2%R+3D	3%R+3D	10mV	10 MΩ/100 pF
500V	1%R+3D	1%R+3D	2%R+3D	2%R+3D	3%R+3D	100 mV	10 MΩ/100 pF
750V	1%R+3D			Not specified		1 V	10 MΩ/100pF
Crest Factor: 3							

Specifications

models

5390 5380 5370 5360

Unless otherwise stated, accuracy specifications apply from 18°C to 28°C. Specifications stated as n%R+nD, mean ±(n% of reading +n least significant digits). Accuracy specifications stated as n%FS, mean ±(n% of Full Scale)

DC VOLTAGE (Auto Manual Ranging)		Accuracy			Resolution	Input Impedance
Ranges						
500 mV	0.025%R+2D	0.025%R+2D	0.05%R+2D	0.1%R+2D	10 µV	10 MΩ or 1 GΩ*
5V 0.025%R+2D	0.025%R+2D	0.025%R+2D	0.05%R+2D	0.1%R+2D	11 MΩ	
50V	0.025%R+2D	0.025%R+2D	0.05%R+2D	0.1%R+2D	1 mV	10 MΩ
500V	0.025%R+2D	0.025%R+2D	0.05%R+2D	0.2%R+2D	10 mV	10 MΩ
1000V	0.025%R+2D	0.025%R+2D	0.05%R+2D	0.3%R+2D	100 mV	10 MΩ
*(10 MΩ only on 5360)						

AC/DC VOLTAGE PROTECTION

Overvoltage Protection	±1100 V DC + AC Peak
Transient Protection	6kV for 10 µs

DC CURRENT (Auto/Manual Ranging)

Ranges		Accuracy		Resolution	Max Burden Voltage
500µA		0.2%R+5D	Not Available	10 nA	700 mV
5 mA		0.2%R+2D	0.2%R+2D	100 nA	700 mV
50mA		0.05%R+2D	0.2%R+2D	1 µA	700 mV
500 mA		0.2%R+2D	0.2%R+2D	10 µA	1.5 V
10 A		0.5%R+2D	0.3%R+2D	1 mA	500 mV

models

5390 5380 5370

AC CURRENT (Auto/Manual Ranging, True RMS) AC or AC + DC
Accuracy at greater than 10% of range, 50,000 counts at Full Scale:

Ranges	DC to 1kHz	1 kHz to 10 kHz	10 kHz to 20 kHz	20 kHz to 30 kHz	Resolution	Input Impedance
500 µA	0.75%R+50D	1.0%R+50D	2.0%R+50D	3.5%R+50D	10 nA	700 mV
5 mA	0.6%R+50D	0.75R+50D	2.0%R+50D	3.0%R+50D	100 nA	700 mV
50 mA	0.6%R+50D	0.75%R+50D	2.0%R+50D	3.0%R+50D	1 µA	700 mV
500 mA	0.7%R+50D	0.75%R+50D	Not specified		10 µA	1.5 V
10 A	1% of FS		Not specified		1 mA	500 mV
Crest Factor: 6						

model

5360

AC CURRENT

Accuracy at greater than 10% of range, 5,000 counts at Full Scale:

Ranges	DC to 5 kHz	Resolution	Max Burden Voltage
5 mA	1.0%R+3D	1 µA	700 mV
50 mA	1.0%R+3D	10 µA	700 mV
500 mA	1.0%R+3D	100 µA	1.5 V
10 A	1% of FS	10 mA	500 mV
Crest Factor: 3			

models

5390 5380 5370 5360

RESISTANCE (Auto/Manual Ranging)

Accuracy		Resolution	Test Current
Ranges			
500 Ω	0.07%R+5D	0.1%R+5D	10 mΩ / 1 mA
5 kΩ	0.07%R+2D	0.1%R+2D	100 mΩ / 100 µA
50 kΩ	0.07%R+2D	0.1%R+2D	1 Ω / 10 µA
500 kΩ	0.07%R+2D	0.1%R+2D	10 Ω / 1 µA
5 MΩ	0.3%R+2D	0.3%R+2D	100 Ω / 100 µA
50 MΩ	1.0%R+2D	1.0%R+2D	1 kΩ / 10 µA

models

5390 5380 5370 5360

CAPACITANCE (Auto/Manual Ranging)

Range	Accuracy	Measurement Resolution	Measurement Current	Max Time
50 nF	1.0%R+2D	1.0%R+2D	10 pF	0.5 sec
500 nF	1.0%R+2D	1.0%R+2D	100 pF	1 µA
5 pF	1.0%R+2D	1.0%R+2D	1 nF	10 µA
50 µF	1.0%R+2D	1.0%R+2D	10 nF	100 µA
500 µF	1.0%R+2D	1.0%R+2D	100 nF	1 mA
5000 µF	1.0%R+2D	2.0%R+2D	1 µF	1 mA
50 mF	1.0%R+2D	2.0%R+2D	10 µF	1mA

models

5390 5380 5370 5360

FREQUENCY (Autoranging)		Accuracy		Resolution	Test Current
Range: 0.6 Hz to 500 kHz					
Accuracy: ±(0.03% rdg + 1 digit)					
Ranges	500 mV (5390, 5370)	5V to 500 V	750 V	10 A	(5390, 5370)
0.6Hz to 5kHz	2% of FS	2% of FS	100 V	2 A	
5 kHz to 50 kHz	5% of FS	5% of FS	250 V	Not specified	
50 kHz to 500 kHz	Not specified	10% of FS	Not specified		

Accessories

SUPPLIED:

Test Leads, Spare Fuses, Instruction Manual

OPTIONAL:

- TL-130A General Purpose DMM Kit
- TP-5300 Platinum Temperature Probe (for 5370)
- AK-5350 Calibration Software (AK-5300 Hardware required)
- AK-5300 Communications Hardware & LabView® drivers

Common Features

CONTINUITY - Threshold: 10Ω to 20Ω
DIODE TEST - Measures forward voltage drop of diode 0 to 1.999V
dB MEASUREMENT - 5390 and 5370 - Measures value relative to a reference from 1 to 9999 Ω, 5380 at 600Ω
PEAK HOLD - Selection: Peak + or Peak- (surge or sag) Acq. Time: < 1rms
DUTY CYCLE: 5390, 5370, 5360-Modes: Selectable %+, ,or %- Min
EVENT COUNTER (Model 5390) - Range: 0 to 99999 (Totalize)
MIN PULSE DURATION: 2 µs
PULSE WIDTH (Model 5390) Modes: Selectable +, - Min. Pulse Width: 20µs Max Pulse Period: 12.5 µs
TEMPERATURE (Model 5370) Using Model TP-5300 Probe (Optional)
RANGE: -200° to +800°C

Computer Interface: RS232 capability built-in. Requires AK-5300

GENERAL

Display: 50,000 count resolution LCD, 0.55" (14mm) digit height, 34 segment analog bargraph
Measurement Rate: 2/sec., 20/sec - bargraph
Power: 9V (NEDA 1604) Battery Life: 500 hrs
Dimensions: 1.57 x 3.23 x 7.44" (40 x 82 x 189mm)
Weight: 14 oz (397g)

Three Year Warranty