



## DM9C Digital Multi-Tester

Compact multimeter for industry or home

- High-resolution, 4000-count autoranging
- 7 functions/23 ranges
- Battery Test Function with Go/NoGo LED indicator
- Industry standard test leads, safety rated
- Protective holster included
- One year warranty

### No hassle warranty

*No waiting.*

*No shipping  
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

#### Included Accessories

Protective holster, test leads, battery and users manual.

#### Optional Accessories

VC30A Vinyl Case



## DM9C Digital Multi-Tester

### General Specifications

Display	3-3/4 digit LCD, 4000 counts
Display Update Rate	2 per sec. nom.
Range Selection	Auto-ranging
Power Supply	Two standard 1.5 V mA batteries
Battery Life	Alkaline 500 hours, approx.
Auto Power Off	15 minutes
Altitude	2000 m
Fuses	500 mA / 600 V, 10 A / 600 V
Operating Temperature	0 °C to + 50 °C, < 70 % R.H. non-condensing
Storage Temperature	- 10 °C to + 60 °C, < 80 % R.H. non-condensing, batteries removed
Dimensions (H x W x D)	14 cm x 7.8 cm x 5 cm (5.45 in x 3.1 in x 1.55 in)
Weight	215 grams (8.2 oz) including battery
Warranty	One-year

### Specifications

Accuracies are indicated at  $\pm$  % of full scale values at 23 °C  $\pm$  5 °C; < 75 % R.H.

Function	Range	Accuracy
<b>Voltage</b>		
DC Voltage	400 mV, 4V, 40V, 400V, 600V	$\pm$ (0.8% rdg + 3 dgts)
Resolution	0.1 mV in 400 mV range	
Input Impedance	10 M $\Omega$	
AC Voltage (40 to 1000 Hz) accuracies apply to sine wave inputs only	400 mV, 4V	$\pm$ (1.3 % rdg + 5 dgts)
Resolution	1 mV in 4000 mV range	
Input Impedance	10 M $\Omega$	
<b>Current</b>		
DC Current	40 mA, 400 mA 10 A*	$\pm$ (1.5% rdg + 3 dgts) $\pm$ (2% rdg + 3 dgts)
Resolution	100 $\mu$ A in 400 mA range	
AC Current	40 mA, 400 mA 10 A*	$\pm$ (1.5% rdg + 3 dgts) $\pm$ (2% rdg + 3 dgts)
Resolution	100 $\mu$ A in 400 mA range	
Burden Voltage	40 mA, 400 mA 10 A	5 mV / mA 40 mV / A
<b>Resistance</b>		
	400 $\Omega$ , 4 k $\Omega$ , 40 k $\Omega$ , 400 k $\Omega$ , 4 M $\Omega$ , 40 M $\Omega$	$\pm$ (1.5 % rdg + 3 dgts)
Open Circuit Voltage	3.2 V DC in all ranges	
<b>Continuity Test</b>		
Buzzer Sounds at	< 60 $\Omega$	$\pm$ (1.0 % rdg + 2 dgts)
<b>Diode Test</b>		
Test Current	0.5 mA nominal	$\pm$ (1.0 % rdg + 2 dgts)
Test Voltage	3.2 V DC nominal	
Display	Forward junction voltage	
<b>Overload Protection</b>		
Voltage, Resistance, Continuity	600 V AC / DC	
Current	500 mA / 600V, 10 A / 600V	

\*10 A for 10 minutes followed by 20 minutes cooling period.

**Amprobe® Test Tools**  
 website: [www.Amprobe.com](http://www.Amprobe.com)  
 email: [info@amprobe.com](mailto:info@amprobe.com)  
 Everett, WA 98203  
 Tel: 877-AMPROBE

**Amprobe® Test Tools Europe**  
 In den Engematten 14  
 79286 Glottertal, Germany  
 Tel.: +49 (0) 7684 8009 - 0

©2007 Amprobe Test Tools. All rights reserved.  
 9/2007 1646350 D-US-N Rev C