


Model 2886 Breakout: BNC (Male) To Minigator Test Clips CE



FEATURES:

- ✓ Converts BNC (female) cables / connectors to minigator test clips for test versatility.
- ✓ BNC connector is molded directly to the wire for pull strength durability and dust and moisture resistance.
- ✓ BNC center contact is gold plated brass for corrosion resistance, low contact resistance and long insertion life.
- ✓ Minigator clips attach to terminals up to .187" (4.75mm) diameter.
- ✓ Black wire is connected to BNC shell, red wire to BNC center contact.

MATERIALS:

BNC: Nickel Plated Brass, Center Contact: Gold Plated Brass *Dielectric*: PTFE *Wire*: 20 AWG, PVC Insulated *Minigators*: Nickel plated steel, Spring: stainless steel *Boot*: Vinyl, color matches color of wire

RATINGS:

Operating Voltage: Hands free testing in controlled voltage environments: 45 VRMS Max. Operating Temperature: +122°F (+50°C) Max.

ORDERING INFORMATION: Model 2886*

* Custom lengths are available, contact Pomona Product Support at: 1-800-241-2060

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com