

FEATURES:

- Kit includes one Oscilloscope probe and below listed accessories..
- Probes are fully insulated and are for use with Fluke ScopeMeter®, 90 Series and 105.

RATINGS:

Performance Specifications:

Attenuation:	Bandwidth (MHz)	Input Impedance	Input Capacitance	Approx. Rise Time	Voltage (V Max.) +	Compensation Range	Cable Length:
		(MW)	(pF)	(nS)		(pF)	
x10	200	10	15	1.8	250	10-60	1.2 Meters

+ Derated with Frequency

ACCESSORIES INCLUDED IN KIT

Description:	Pomona Reordering Part Number:
Full Acc. Kit	6034-2 (Red), 6034-8 (Gray)
Sprung Hook	6095-2 (Red), 6095-8 (Gray)
Trimmer Tool	6096
IC Tip	6097
Insulating Tip	6098
BNC Adapter	5822
Replacement Tip	6099
Ground Lead	5825
Sheathed Banana	6100
Plug Adapter	

ORDERING INFORMATION: Model 6006-*, 6033 (Kit with 1 Red, 1 Gray probe with accessories)

* =Color, -2 Red, -8 Gray

All dimensions are in inches. Tolerances (except noted): $.xx = \pm.02$ " (,51 mm), $.xxx = \pm.005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

6/9/99	Sales: 800-490-2361	Fax: 888-403-3360				
SY/EH/LS	Technical Assistan	ce: 800-241-2060				
C:\Laura Goldberg\FlukeDataSheet\d6006 6033 1 01.doc						