

CHEMTRONICS[®]

Technical Data Sheet

TDS # CT40

CircuitWorks[®] Heat Sink Grease

PRODUCT DESCRIPTION

CircuitWorks[®] Heat Sink Grease silicone compound facilitates heat transfer away from electrical/electronic components. This heavy consistency material is thickened with a heat conductive metal oxide filler to maintain a positive heat sink seal in electrical/electronic equipment.


- Excellent conductivity
- Meets MIL-C-47113
- Noncorrosive
- High dielectric strength
- Low bleed
- Stable from -73°C to 200°C
- Nonflammable

TYPICAL APPLICATIONS

CircuitWorks[®] Heat Sink Grease may be used for electronics and applications including:

- Effective Thermal Coupler For Any Heat Sink Device
- Nonflammable Coating Protection
- High Voltage Corona Protection
- Excellent for Improving Readings on Contact Type Thermocouples

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Color	White
Specific Gravity @ 25°C (77°F)	2.6
Usable Temperature Range	-73°C (-100°F) to 200°C (392°F)
Dielectric Strength, v/mil	500
Dielectric Constant @ 100 Hz	4.4
Dissipation Factor @ 100 Hz	0.005
Volume Resistivity, ohm-cm	1 x 10 ¹⁴
Arc Resistance, seconds	120
Thermal Conductivity,	
Cal-cm/sec-cm² -°C	1.5 x 10 ⁻³
BTU-in/hr-ft² -°F	4.35
W/m²°K	0.63
Shelflife	5 years
RoHS/WEEE	
Status	

COMPATIBILITY

CircuitWorks[®] Heat Sink Grease is generally compatible with most materials used in printed circuit board fabrication. As with any silicone compound, compatibility with substrate must be determined on a non-critical area prior to use.

Material	Compatibility
Ceramic	Good
Clean Metals	Good
Glass	Good
Natural Fibers	Good
Silicone Resins	Good
Painted Surfaces	Good
Plastic Surfaces	Good
Synthetic Fibers	Good
Vulcanized Silicone Rubber	Good
Wood	Good

ENVIRONMENTAL IMPACT DATA

ENVIRONMENTAL IMPACT DATA			
CFC	0.0%	VOC	0.0%
HCFC	0.0%	HFC	0.0%
Cl. Solv.	0.0%	ODP	0.00

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. ITW CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

MANUFACTURED BY:

ITW CHEMTRONICS®
 8125 COBB CENTER DRIVE
 KENNESAW, GA 30152
 1-770-424-4888

REV. (06/06)

Chemtronics® and CircuitWorks® are registered trademarks of ITW Chemtronics. All rights reserved.

USAGE INSTRUCTIONS

For industrial use only.

Read MSDS carefully prior to use.

Contact ITW Chemtronics® for complete usage and application instructions. When using CircuitWorks® Heat Sink Grease, follow these guidelines: Apply to all mounting and threaded surfaces of the device and the chassis. Apply by pushing product ahead of neck.

Dispensing: CircuitWorks® Heat Sink Grease is a ready-to-use one-component material. Collapsible tubes may be squeezed by hand or with the aid of mechanical wringers.

AVAILABILITY

CT40-5 5 oz. Tube

TECHNICAL & APPLICATION ASSISTANCE

ITW Chemtronics® provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

<u>DISTRIBUTED BY:</u>