# **High Performance BGA Cooling Solu**tions w/ Thermal Tape Attachment\*

## DIGI-KEY PART # ATS1274-ND

ATS PART # ATS-55330D-C2-R0


#### **Features & Benefits**

High efficiency cross-cut fin design provides low pressure drop characteristics

Large surface area increases heat sink performance

Designed for BGAs and surface mount packages

Comes preassembled with high performance thermal interface material







## **Thermal Performance Table**

AIR VELOCITY		THERMAL RESISTANCE		
FT/MIN	M/S	°C/W (UNDUCTED)	°C/W (DUCTED)	
200	1.0	12.3	NA	
300	1.5	NA		
400	2.0	NA		
500	2.5	NA		
600	3.0	NA		
700	3.5	NA		
800	4.0	NA		

### Product Details<sup>†</sup>

DIMENSION A	DIMENSION B	DIMENSION C <sup>§</sup>	DIMENSION D	TIM <sup>‡</sup>	FINISH
33	33	9.5	N/A	C675	BLACK-ANODIZED

For further technical information, please contact Advanced Thermal Solutions, Inc. at 1-781-769-2800 or www.qats.com

- \* RoHS Compliant
- ‡ TIM = Thermal Interface Material
- † Dimensions are measured in millimeters
- ♦ Dimensions A & B refer to component size
- § Dimension C = the height of the heat sink shown above and does not include the height of the attachment method



