# Low Profile, High Performance Cooling Solutions w/Thermal Tape Attachment\*

### DIGI-KEY PART # ATS1376-ND

ATS PART # ATS-60000-C2-R0


#### **Features & Benefits**

bluelCE™ heat sinks feature an ultra low profile for tough-to-cool applications

Designed for high performance in low air velocities

Ideal for telecommunications applications where space is limited

Comes preassembled with high performance thermal interface material



# **Thermal Performance Table**

AIR VELOCITY		THERMAL RESISTANCE		
FT/MIN	M/S	°C/W (UNDUCTED)	°C/W (DUCTED)	
200	1.0	14.8	7.8	
300	1.5	11.6		
400	2.0	9.6		
500	2.5	8		
600	3.0	6.9		
700	3.5	5.9		
800	4.0	5.3		

## **Product Details**†

DIMENSION A	DIMENSION B	DIMENSION C <sup>§</sup>	DIMENSION D	TIM <sup>‡</sup>	FINISH
25.2	25.2	4	34.8	C675	BLUE-ANODIZED

For further technical information, please contact Advanced Thermal Solutions, Inc. at **1-781-769-2800** or **www.qats.com** 

- \* RoHS Compliant
- ‡ TIM = Thermal Interface Material
- † Dimensions are measured in millimeters
- § Dimension C = the height of the heat sink shown above and does not include the height of the attachment method



