


[COMPANY](#)
[PRODUCTS](#)
[DISTRIBUTORS](#)
[CONTACT](#)
[SHOP AT STEINEL](#)

[Products](#) > [Heat Guns](#)
[Heat Guns](#)
[Glue Guns](#)
[Exterior Lights](#)
[Sensors](#)
[Voltage Testers](#)

## ELECTRONIC HEAT GUNS



**STEINEL Electronic Heat Guns** are ideal for applications requiring precise temperature control such as shrink tubing or welding plastics. Electronic control makes it possible to restrict airflow through pin-point reduction nozzles used for soldering sink wire connectors, de-soldering circuit boards, shrinking small diameter tubes. Also can be used to weld with narrow-slit nozzles.

Electronic thermo couple control is what sets these heat guns apart. This feature continuously monitors and adjusts output to maintain a constant temperature and avoid overheating.

You can count on **STEINEL** heat guns for precision, durability and long life.



Roofing



Welding Plastic Materials



Butt-welding PVC



Soldering & De-soldering



Shaping Plastic



Sealing Vinyl Flooring



Applying Shrink Tubes

### HG 3002 LCD

Electronically monitored heat gun with variable airflow and digital temperature display for precise control.

<b>Temperature</b>	Continuously variable 120°F – 1100°F.
<b>Airflow</b>	Continuously variable up to 17.6 cfm with selectable cool air stage.
<b>LCD</b>	Displays temperature output in 10°F increments.
<b>Double Insulated Power Cord</b>	Rubber construction for increased safety.
<b>Output</b>	1,500 watts.
<b>Voltage</b>	120 VAC / 60 Hz.
<b>Certifications</b>	UL / CSA.
<b>Full One Year Warranty</b>	Refer to owner's manual for details.
<b>Accessories</b>	Accepts a full range of nozzles and accessories.



### HG 2002 LE

Electronically monitored heat gun with 3-stage airflow and LED temperature range indicator.

<b>Temperature</b>	Continuously variable 120°F – 1100°F.
<b>3-Stage Airflow</b>	Stage 1: cool air at 17.6 cfm Stage 2: 9.5 cfm Stage 3: 17.6 cfm

<b>LED Display</b>	Diodes indicate temperature range selected.
<b>Double Insulated Power Cord</b>	Rubber construction for increased safety.
<b>Output</b>	1,500 watts.
<b>Voltage</b>	120 VAC / 60 Hz.
<b>Certifications</b>	UL / CSA.
<b>Full One Year Warranty</b>	Refer to owner's manual for details.
<b>Accessories</b>	Accepts a full range of nozzles and accessories.



## HG 2000 E

**Electronically controlled heat gun with constant air flow. Lightweight, ergonomically designed.**

<b>Temperature</b>	Continuously variable 120°F – 1100°F.
<b>Constant Airflow</b>	14.8 cfm.
<b>Ergonomic Design</b>	Lightweight (21.7 oz.) and easy to use, even in tight quarters.
<b>Double Insulated Power Cord</b>	Rubber construction for increased safety.
<b>Output</b>	1,500 watts.
<b>Voltage</b>	120 VAC / 60 Hz.
<b>Certifications</b>	UL / CSA.
<b>Full One Year Warranty</b>	Refer to owner's manual for details.
<b>Accessories</b>	Accepts a full range of nozzles and accessories.



## HG 1802 E

**Electronically monitored heat gun with variable temperature and 3 stage airflow.**

<b>Temperature</b>	Continuously variable 120°F – 1100°F.
<b>3 Stage Airflow</b>	Stage 1: cool air at 17.6 cfm Stage 2: 9.5 cfm Stage 3: 17.6 cfm
<b>Double Insulated Power Cord</b>	Rubber construction for increased safety.
<b>Output</b>	1,500 watts.
<b>Voltage</b>	120 VAC / 60 Hz.
<b>Certifications</b>	UL / CSA.
<b>Full One Year Warranty</b>	Refer to owner's manual for details.
<b>Accessories</b>	Accepts a full range of nozzles and accessories.



