

WS 6 End Stripper

BUSHING SELECTION TABLE

These tables should only be used as a guide. Cable samples should be provided to Ripley to ensure proper sizing.

Cable O.D. to be stripped		Bushing #	Cable O.D. to be stripped		Bushing #
(inch)	(mm)		(inch)	(mm)	
0.961 - 0.985	24.41 - 25.02	WS 6-1.000	1.436 - 1.460	36.47 - 37.08	WS 6-1.475
1.986 - 1.010	25.04 - 25.65	WS 6-1.025	1.461 - 1.485	37.11 - 37.72	WS 6-1.500
1.011 - 1.035	25.68 - 26.29	WS 6-1.050	1.486 - 1.510	37.74 - 38.35	WS 6-1.525
1.036 - 1.060	26.31 - 26.92	WS 6-1.075	1.511 - 1.535	38.38 - 38.99	WS 6-1.550
1.061 - 1.085	26.95 - 27.56	WS 6-1.100	1.536 - 1.560	39.01 - 39.62	WS 6-1.575
1.086 - 1.110	27.58 - 28.19	WS 6-1.125	1.561 - 1.585	39.65 - 40.26	WS 6-1.600
1.111 - 1.135	28.22 - 28.83	WS 6-1.150	1.586 - 1.610	40.28 - 40.89	WS 6-1.625
1.136 - 1.160	28.85 - 29.46	WS 6-1.175	1.611 - 1.635	40.92 - 41.53	WS 6-1.650
1.161 - 1.185	29.49 - 30.10	WS 6-1.200	1.636 - 1.660	41.55 - 42.16	WS 6-1.675
1.186 - 1.210	30.12 - 30.73	WS 6-1.225	1.661 - 1.685	42.19 - 42.80	WS 6-1.700
1.211 - 1.235	30.76 - 31.37	WS 6-1.250	1.686 - 1.710	42.82 - 43.43	WS 6-1.725
1.236 - 1.260	31.39 - 32.00	WS 6-1.275	1.711 - 1.735	43.46 - 44.07	WS 6-1.750
1.261 - 1.285	32.03 - 32.64	WS 6-1.300	1.736 - 1.760	44.09 - 44.70	WS 6-1.775
1.286 - 1.310	32.66 - 33.27	WS 6-1.325	1.761 - 1.785	44.73 - 45.34	WS 6-1.800
1.311 - 1.335	33.30 - 33.91	WS 6-1.350	1.786 - 1.810	45.36 - 45.97	WS 6-1.825
1.336 - 1.360	33.93 - 35.54	WS 6-1.375	1.811 - 1.835	46.00 - 46.61	WS 6-1.850
1.361 - 1.385	34.57 - 35.18	WS 6-1.400	1.836 - 1.860	46.63 - 47.24	WS 6-1.875
1.386 - 1.410	35.20 - 35.81	WS 6-1.425	1.861 - 1.885	47.27 - 47.88	WS 6-1.900
1.411 - 1.435	35.84 - 36.45	WS 6-1.450			