

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION, 19 .
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.


| LOC | DIST | REVISIONS | | | | | |
|-----|------|-----------|-----|--------------------------|-----------|-----|------|
| | | P | LTR | DESCRIPTION | DATE | DWN | APVD |
| CE | 16 | | E | REVISED PER 0A00-0067-00 | 08FEB2001 | TA | SB |

△1 COLOR LISTED IS AFTER CURE.

| | | | | | | | | |
|----------|---|--------------------------|---------------------|----------|----------|---------------------------|--------------------------------|-------------|
| OBSOLETE | MANUFACTURING AND FIELD USE | ALL | 15MIN 100C | 2 HR | AMBER | 25 2GR PKS | 250 | 501195-7 |
| OBSOLETE | FIELD USE OR WHEN A FAST CURE AT ROOM TEMP REQUIRED | FSMA | 45MIN 25C | 2 MIN | STRAW | 25 2GR PKS | 125 | 501195-6 |
| OBSOLETE | FOR USE IN HIGH TEMP ENVIRONMENT | FSMA | 15MIN 100C | 40 MIN | AMBER | 25 2GR PKS | 250 | 501195-5 |
| | MANUFACTURING AND FIELD USE | FSD, RSD, ST STYLE, FSMA | 24HR 25C OR 2HR 65C | 30 MIN | BLUE | 25 2GR PKS | 250 | 501195-4 |
| OBSOLETE | FIELD USE OR WHEN A FAST CURE AT ROOM TEMP REQUIRED | FSMA | 45MIN 25C | 2 MIN | STRAW | 10 2GR PKS | 50 | 501195-3 |
| OBSOLETE | FOR USE IN HIGH TEMP ENVIRONMENT | FSMA | 15MIN 100C | 40 MIN | AMBER | 25 7GR PKS | 500 | 501195-2 |
| OBSOLETE | MANUFACTURING AND FIELD USE | FSD, RSD, ST STYLE, FSMA | 24HR 25C OR 2HR 65C | 30 MIN | BLUE | 25 7GR PKS | 500 | 501195-1 |
| | APPLICATION | CONNECTOR TYPE | CURE TIME | POT LIFE | △1 COLOR | NO. OF PACKS WT. PER PACK | APPROX # OF CONNECTORS PER BOX | PART NUMBER |

501195

B

| | | | |
|--|---|--|--|
| <small>THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.</small> | | DWN S.URICH 30NOV95 CHK R.RENN 30NOV95 APVD N.MILLER 30NOV95 | AMP AMP Incorporated Harrisburg, PA 17105-3608 |
| DIMENSIONS: mm  | TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±- FINISH - | PRODUCT SPEC - APPLICATION SPEC - WEIGHT - | ADHESIVE, EPOXY SIZE A2 CAGE CODE 00779 DRAWING NO. C-501195 SCALE 1:1 SHEET 1 OF 1 REV E |
| MATERIAL - | | CUSTOMER DRAWING | |